

Model JSB-291

USB 20 Amp Single (1) Relay SPDT Module

Overview

The JSB-291 USB Relay module provides two or three (2/3) SPDT relays for connection to user devices. The relay module programming interface is easy to use from Visual Basic and Visual C++ via a standard windows DLL with sample source included. Any programming language that supports calls to Windows DLL can also be used. Each module has an unique serial number string which allows multiple USB devices to be controlled by the host USB controller as individual devices. Wire connection to the module relay contacts is with screw type high quality terminal blocks

Specification

AC Ratings: 20A @ 125VAC resistive 16A @ 240VAC resistive	Sample applications included Operating Temperature -30 to 70 deg C
Max Voltage 125VDC 250VAC	Self powered from USB
Contact Resistance: 100mOhm Max	Windows 98/ME/2K/XP/Vista drivers
Relay Closing Time: 15 milliseconds	USB test cable included
Relay Releasing Time: 8 milliseconds	Weight 6 oz
Material Gold-clad silver alloy	

Ordering Information

Model Number	Description	Cost each
JSB291-02	USB 2 Relay Module	\$60.00
JSB291-03	USB 3 Relay Module	\$75.00

Accessory Items

The following items are offered as a customer convenience, there are many sources of compatible products

AY-AB-06	USB 6 foot cable	\$3.00
----------	------------------	--------

Specifications subject to change without notice
Page Last Updated Feb 8, 2008

J-Works, Inc

11024 Balboa Blvd. #402
Granada Hills, CA 91344
818 364-0915 voice 818 364-0912
sales@j-works.com